




THE VALUE LEADER IN SOLAR WATER HEATING TECHNOLOGY



SUN EARTH INC. EMPIRE SERIES SPECIFICATIONS

| SunEarth Model No. | Width Inches | Length Inches | Depth Inches | Gross Area Sq Ft | Net Aperture Sq Ft | Dry Weight, Lbs. | Fluid Capacity U.S. Gallons | Design Flow Rate GPM | Pressure Drop at Design Flow Rate in PSIG | Max Flow Rate GPM | Maximum Operating Press PSIG | Std. Header Width, Inches | Std. Header Diameter, Inches Nominal | Header Center to Center, Inches |
|--------------------|--------------|---------------|--------------|------------------|--------------------|------------------|-----------------------------|----------------------|---|-------------------|------------------------------|---------------------------|--------------------------------------|---------------------------------|
| EC/EP21 | 40 | 76 | 3 1/4 | 21.12 | 18.70 | 70 | 0.72 | 0.54 | 0.003 | 12 | 160 | 43 3/8 | 1 | 71.25 |
| EC/EP24 | 36 1/8 | 98 1/4 | 3 1/4 | 24.61 | 21.88 | 80 | 0.78 | 0.62 | 0.005 | 12 | 160 | 39 3/4 | 1 | 93 5/8 |
| EC/EP32 | 48 1/8 | 98 1/4 | 3 1/4 | 32.79 | 29.81 | 106 | 1.00 | 0.83 | 0.006 | 12 | 160 | 51 3/8 | 1 | 93 5/8 |
| EC/EP40 | 48 1/8 | 122 1/4 | 3 1/4 | 40.81 | 37.33 | 141 | 1.20 | 1.04 | 0.009 | 12 | 160 | 51 3/8 | 1 | 115 5/8 |
| EC/EP40-1.5 | 48 1/8 | 122 1/4 | 3 1/4 | 40.81 | 37.33 | 150 | 1.61 | 1.04 | 0.006 | 25 | 160 | 51 3/8 | 1 1/2 | 115 5/8 |

MODEL EC

THERMAL PERFORMANCE RATINGS*

MODEL EP

| Category (Ti-Ta) <small>Ti = inlet fluid temp Ta = ambient air temp</small> | Btu/ft ² /Day | | |
|--|--------------------------|-------------------|------------|
| | CLEAR DAY | MILDLY CLOUDY DAY | CLOUDY DAY |
| A(-9°F) | 1,332 | 1,005 | 680 |
| B(9°F) | 1,218 | 890 | 565 |
| C(36°F) | 1,040 | 720 | 402 |
| D(90°F) | 699 | 405 | 127 |
| E(144°F) | 390 | 137 | - |

| Category (Ti-Ta) <small>Ti = inlet fluid temp Ta = ambient air temp</small> | Btu/ft ² /Day | | |
|--|--------------------------|-------------------|------------|
| | CLEAR DAY | MILDLY CLOUDY DAY | CLOUDY DAY |
| A(-9°F) | 1,284 | 971 | 659 |
| B(9°F) | 1,169 | 854 | 542 |
| C(36°F) | 984 | 677 | 372 |
| D(90°F) | 619 | 343 | 89 |
| E(144°F) | 280 | 62 | - |

A-Pool Heating (Warm Climate) B-Pool Heating C-Water Heating (Warm Climate) D-Water Heating (Cool Climate) E-Air Conditioning/Industrial Process Heat.
Thermal performance is obtained by multiplying the collector output for the appropriate application and insolation level by the total gross collector area.
 *Collector ratings are derived from the Solar Rating & Certification Corp (SRCC) Document RM-1 and Standard OG-100.

ENGINEERING SPECIFICATIONS

(Performance specifications subject to testing error of +/- 3%)

The following shall be the specifications for the solar collectors. Collectors shall be SunEarth Empire model _____, and shall be of the glazed liquid flat plate type. Collectors shall be tested in conformance with ASHRAE 93-1986 and SRCC 100-81. The collectors shall be certified by the Solar Rating and Certification Corporation (SRCC) and the Florida Solar Energy Center (FSEC).

GENERAL

The dimensions of the collector shall be _____ inches in length, _____ inches in width and 3 1/4 inches in depth. The collector casing shall be an anodized aluminum extrusion (alloy 6063 T5), minimum thickness .060 inch, with an architectural dark bronze finish. The casing shall have notched framewalls for ease of plate removal and reinstallation. Sheet metal screwed fasteners shall be stainless steel (18-8 #10). The backsheet shall be painted textured aluminum not less than .014 inch thickness. A 1 inch vent plug shall be installed in each of the four corners of the backsheet to minimize condensation.

GLAZING

The collector glazing shall be one sheet of low iron tempered glass, with a minimum of 1/8 inch thickness (5/32 inch on EC/EP 40), and a minimum transmissivity of 91 percent (89 on EC/EP 40). The glazing shall be thermally isolated from the casing by a continuous EPDM gasket. There shall be a continuous secondary silicone seal between the glass and casing capstrip to minimize moisture from entering the casing.

INSULATION

The insulation shall be foil-faced polyisocyanurate foam sheathing board of a minimum 1 inch thickness, siliconed in place to the aluminum backsheet, covered by low-binder fiberglass of a minimum 1 inch thickness, providing

thermal isolation of the foam from the absorber plate. Total thermal resistance shall be a minimum of R-12. The sides and ends of the collector shall be insulated with a minimum of 1 inch foil-faced polyisocyanurate foam sheathing board.

ABSORBER PLATE AND PIPING



The absorber shall consist of a roll-formed copper plate of no less than .008 inch thickness. Risers shall be a minimum of 1/2 inch O.D. Type M copper tubing on no more than 4 1/2 inch centers continuously soldered to the plate utilizing a non-corrosive solder paste with a melting point of 460°F. The risers shall be brazed to 1 1/8" O. D. Type M (1 5/8" O.D. on EC/EP40-1.5) copper manifolds utilizing a copper phosphorous brazing alloy with no less than 15 percent silver content, and conforming to the American Welding Society's BCuP-5 classification. EPDM grommets shall isolate the manifold from the aluminum casing. The absorber plate shall be designed for 160 psig maximum operating pressure.

ABSORBER COATING AND PERFORMANCE CURVE

A) Black Chrome (EC Series): The absorber coating shall be black chrome on nickel with a minimum absorptivity of 95 percent and a maximum emissivity of 12 percent. The instantaneous efficiency of the collector shall be a minimum Y-intercept of 0.714 and a slope of no less than -0.7271 (BTU/ft²-hr)/F.

B) Moderately Selective Black Paint (EP Series): The absorber coating shall be a moderately-selective black paint with a minimum absorptivity of 94 percent and a maximum emissivity of 56 percent. The instantaneous efficiency of the collector shall have a minimum Y-intercept of 0.682 and a slope of no less than -0.7995 (BTU/ft²-hr)/F.

Due to SunEarth's policy of continuous product improvement, specifications are subject to change without notice.

| | |
|---|--|
| <p>MANUFACTURED BY:</p>  <p>SUN EARTH INC. 4315 Santa Ana St. • Ontario, CA 91761 (909) 605-5610 • Fax (909) 605-5613 www.sunearthinc.com</p> | <p>AVAILABLE FROM:</p> <div style="text-align: right;">  </div> <p>RECYCLED PAPER—SOY BASED INK</p> |
|---|--|